

Light-Sky Led Lights		
Model&Picture	Specification Parameter	Warranty
<p>CLS-WK</p> 	<p>LED Wall Pack Light Power: 20W/40W/60W/80W/100W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50/60HZ Luminous Efficiency: 130-140lm/w Color temperature: 2700K-6500K IP Grade : IP65 Beam Angle: 90°*120° Housing color: Black, Gray, White with light sensor Certified: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-UFOH</p> 	<p>LED UFO High Bay Light Power: 100W/150W/200W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50/60HZ Luminous Efficiency: 180lm/w-190lm/w Color temperature: 2700K-6500K IP Grade : IP65 Beam Angle: 80°, 110° Certified: CE, ROHS, ETL, DLC, SAA, UL, EMC Application: Warehouse, Station, Gym, Industrial house</p>	5 years
<p>CLS-FL</p> 	<p>Adjustable LED Flood Light Power: 50W/100W/150W/200W/300W/500W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage : AC90-305V, 50/60HZ Luminous Efficiency: 130-140lm/w Color temperature: 2700K-6500K IP Grade: IP65 Beam Angle: SMD3030: 60°, 90°, 30° x 70° SMD5050: 12°, 30°, 60°, 90° Housing color: Black Certificates: CE, ROHS, ETL, DLC, SAA, UL, EMC Application: Park, Tunnel, Billboard, Outdoor stadium and Outdoor place</p>	5 years
<p>CLS-SL</p> 	<p>Solar Led Street Light Power: 20w/30w/40w/50w/60w/70w/80w/100w Solar Battery Panel Max Power: 36w/90w Battery:Lithium 12V,48AH Using lifespan: 50000hours Charging: 6-10 hours effective sunlight Work mode: PIR+Daylight Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC Lighting time: 3-5 raining days Mounting height: 9-10M, Mounting distance: 30-35M</p>	5 years
<p>CLS-HB-W-GS23</p> 	<p>LED Linear High Bay Light Power: 50W/100W/150W/200W/250W/300W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50/60HZ Beam Angle: 30° x 70°, 30°, 60°, 90°, 60° x 120° Luminous Efficiency: 130-140lm/w Color temperature: 2700K-6500K IP Grade: IP65 Installation way: wall mounted, ceiling hanging Certificate: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-TG3A</p> 	<p>LED Flood Light Power: 100W/150W/200W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Working voltage: AC90-305V, 50-60HZ LEDs efficiency: 130-140lm/w Material: Glass Beam Angle +Al Body Beam Angle: 120° Color temperature: 2700K-6500K Lifetime: >50000hours IP Grade: IP65 Certificates: CE, ROHS, ETL, DLC, SAA, UL, EMC Application: Park, Tunnel, Billboard, Stadium and Outdoor Place</p>	5 years

Light-Sky Led Lights		
Model&Picture	Specification Parameter	Warranty
<p>CLS-SL409</p> 	<p>LED Flood Light Power: 100W/150W/200W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V,50/60HZ Beam Angle: 90° x 120° Luminous Efficiency: 130-140lm/w Color temperature:2700K-6500K IP Grade : IP65 With different Arm/Connector for different Pole Certificate: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-PL409</p> 	<p>LED Parking Lot Light Power: 80W/100W/120W/150W/200W Input Voltage: AC100-277V,50/60HZ Beam Angle: 90° x 120° Luminous Efficiency : 130-140lm/w Color temperature: 2700K-6500K IP Grade : IP65 With different Arm/Connector for different Pole Certificate: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-SLL</p> 	<p>LED Flood Light Power:100W-960W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50/60HZ Beam Angle: 30°, 60°, 90°, 80° x 140° Luminous Efficiency : 130-140lm/w Color temperature: 2700K-6500K IP Grade : IP65 Certificate: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-TN408</p> 	<p>LED Tunnel Light Power: 50W/100W/150W/200W/240W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50-60HZ Beam Angle: 60°, 90°, 80° x 150°, 90° x 120° Luminous Efficiency :130-140lm/w Color temperature:2700K-6500K Shell: Black die-casting aluminum Beam Angle: PC Beam Angle Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-FTL</p> 	<p>LED Flood Light Power: 300W/600W/900W/1200W Led driver: Mean Well Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage : AC90-305V, 50-60HZ Beam Angle: 10°, 25°, 60° Luminous Efficiency :130-140lm/w Color temperature: 2700K-6500K Shell: Black die-casting aluminum IP Grade : IP65 Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-HB-GKL</p> 	<p>Indoor UFO LED High Bay Light Power: 60W/100W/150W/200W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Working voltage: AC90-305V, 50-60HZ LEDs efficiency: 130-140lm/w Material: Glass + Al Body Beam Angle: 25°, 60°, 90°, 100°, 110° Color temperature: 2700K-6500K IP Grade: IP54 Body & Shade Material: Aluminum Certificaties:CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-HB</p> 	<p>LED High Bay Light Power: 100W/150W/200W/240W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Working voltage: AC90-305V, 50-60HZ LEDs efficiency: 130-140lm/w Material: Glass Beam Angle +Al Body Beam Angle: 90°, 120° Color temperature: 2700K-6500K IP Grade: IP65 Body & Shade Material: Aluminum Certificaties: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years

Light-Sky Led Lights		
Model&Picture	Specification Parameter	Warranty
<p>CLS-UFOHX</p> 	<p>LED UFO High Bay Light Power: 50W/120W/100W/150W/200W Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50/60HZ Luminous Efficiency: 130-140lm/w Color temperature: 2700K-6500K IP Grade: IP65 Beam Angle: 60°, 90°, 120° Certified: CE, ROHS, ETL, DLC, SAA, UL, EMC Application: Warehouse, Station, Gym, Industrial house</p>	5 years
<p>CLS-LSF</p> 	<p>Led Street Light Power: 50w/100w/150w/200w/250w/300w Led driver: Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: AC90-305V, 50-60HZ LED efficiency: 130-140LM/w Color temperature: 2700K-6500K IP Grade : IP65 Viewing angle: 140° x 80° Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-BA07A</p> 	<p>Led Flood Light Power: 200W/360W/500W/1000W Led driver: Mean Well Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: VAC90-305V, 50-60HZ LED efficiency:130-140lm/w or 180-190lm/w Color temperature: 2700K-6500K IP Grade: IP65 Beam Angle: 3535 leds: 12° 5050 leds: 30°, 60°, 90°, 30°x70° 3030 leds: 60°, 90° Lifetime:>50000hours Material: PC Lens + Al Body Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
<p>CLS-LBA07A</p> 	<p>Linear Led Flood Light Power: 120W/180W/240W/360W Led driver: Mean Well Led driver/ 0-10v led dimming driver/ Dali Dimming led driver Input Voltage: VAC90-305V, 50-60HZ LED efficiency: 130-140lm/w or 180-190lm/w Color temperature:2700K-6500K IP Grade : IP65 Beam Angle: 5050 leds: 30°, 60°, 90°, 30°x70° 3030 leds: 60°, 90° Lifetime: >50000hours Material: PC Lens +Al Body Certification: CE, ROHS, ETL, DLC, SAA, UL, EMC</p>	5 years
1. Quotation term: EXW (factory price)	2. Payment: T/T or Western Union or LC	
3. MOQ: 1-6 Piece	4. Delivery time: Within 7-10 working days after payment received	